



Smart - Indoor

Condizionatori da Parete - Wall Mounted A/C - Wandklimageräte - Aires Acondicionados para Montaje en la Pared

Caratteristiche Generali

- Installazione orizzontale
- Capacità frigorifere: 420W
- Alimentazione 230 50/60 Hz
- Termostato meccanico



General Features

- Horizontal installation
- Cooling capacity 420 W
- Power Supply 230 50/60 Hz
- Mechanical thermostat

Allgemeine Merkmale

- Horizontale Installation
- Kälteleistung 420 W
- Spannungsversorgung 230V 50/60Hz
- Mechanisches Thermostat

Características Generales

- Instalación horizontal
- Capacidad frigorífica: 420W
- Alimentación 230 50/60 Hz
- Termostato mecánico

OPTIONAL

CODICE - CODE - ARTIKELNUMMER - CODIGO

Colore Speciale - Special Colour
Sonderfarbe - Color especial

Carpenteria - Housing - Gehäuse - Caja
INOX AISI304

EVE03H

OCAVNS02

OCAVISM

Certificazioni - Certifications - Zertifizierungen - Certificaciones

- CE
- EAC





EVE03H



CODICE - CODE - ARTIKELNUMMER - CÒDIGO	M.U.	EVE03H3220
Tensione nominale - Rated voltage - Nennspannung - Tensión nominal	V. ~	230 . 1
Frequenza nominale - Nominal frequency - Nennfrequenz - Frecuencia nominal	Hz	50/60
Potenza frigorifera - Cooling capacity - Kühlleistung - Potencia frigorífica	L35L35 W	420
Potenza frigorifera - Cooling capacity - Kühlleistung - Potencia frigorífica	L35L50 W	280
Potenza assorbita - Power consumption - Leistungsaufnahme - Potencia absorbida	L35L50 W	300
Corrente assorbita - Current consumption - Stromaufnahme - Corriente absorbida	CE L35L35 A	1,2
Corrente di avviamento - Start-up current - Anlaufstrom - Corriente de puesta en marcha	CE A	3
Taratura del dispositivo di protezione - Protection device calibration - Kalibrierung der Schutzeinrichtung - Calibración del dispositivo de protección	CE A	2
Temp. interne di funzionamento - Internal operating temp. - Interne Betriebstemperatur - Temp. internas de funcionamiento	min/max °C	+25 / +45
Temp. esterne di funzionamento - External operating temp - Externe Betriebstemperatur - Temp. externas de funcionamiento	min/max °C	+20 / +55
Grado di protezione circuito interno - Internal circuit protection rating - Schutzgrad interner Kreislauf - Grado de protección del circuito interno	CE IP	54
Pressione sonora esterna - External sound pressure - Externer Schalldruck - Presión sonora externa	dB(A)	60
Altezza / Larghezza / Profondità - Height / Width / Depth - Höhe / Breite / Tiefe - Altura / Anchura / Profundidad	mm	300 x 500 x 140
Peso - Weight - Gewicht - Peso	kg	17

Smart Layout

